

S/N 10/032,700
Ref. No.: 659-911
Client Ref. No.: K-C 17154

IN THE CLAIMS:

Please amend claims 2-15, 17-20, 22-28 and 30-37. Claims 38-40 are withdraw so that the claims read as follows:

1. (Original) A refastenable absorbent garment comprising:
 - a first body panel having a body side and a garment side;
 - a second body panel having a body side and a garment side; and
 - a fastener member attached to said body side of said first body panel and releasably attached to said body side of said second body panel.
2. (Currently Amended) The refastenable absorbent garment invention of claim 1 wherein said fastener member is fixedly attached to said body side of said first body panel.
3. (Currently Amended) The refastenable absorbent garment invention of claim 2 wherein said fastener member is bonded to said body side of said first body panel.
4. (Currently Amended) The refastenable absorbent garment invention of claim 3 wherein said fastener member is ultrasonically bonded to said body side of said first body panel.
5. (Currently Amended) The refastenable absorbent garment invention of claim 1 wherein said fastener member is releasably attached to said body side of said first body panel.
6. (Currently Amended) The refastenable absorbent garment invention of claim 1 wherein said fastener member comprises a first portion attached to said body

S/N 10/032,700

Ref. No.: 659-911

Client Ref. No.: K-C 17154

side of said first body panel and a second portion releasably attached to said body side of said second body panel, wherein said first and second portions are hingedly connected.

7. (Currently Amended) The refastenable absorbent garment invention of claim 6 wherein each of said first and second body panels comprise an outboard side edge and wherein each of said first and second portions comprise an inboard and an outboard edge, wherein said outboard edges of said first and second portions are positioned closer to said outboard side edges of said first and second body panels, respectively, than are said inboard edges of said first and second portions, and wherein said outboard edges of said first and second portions are hingedly connected.

8. (Currently Amended) The refastenable absorbent garment invention of claim 6 wherein said first and second portions comprise first and second folds hingedly connected along a folded edge.

9. (Currently Amended) The refastenable absorbent garment invention of claim 6 wherein said first portion is bonded to said second portion.

10. (Currently Amended) The refastenable absorbent garment invention of claim 6 wherein each of said first and second portions have a body side and a garment side, wherein said body sides of each of said first and second portions are in contact when said absorbent garment is in a folded configuration with said body sides of said first and second body panels in contact, and wherein said garment side of said first portion is attached to said body side of said first body panel and wherein said garment side of said second portion is releasably engaged with said body side of said second body panel.

S/N 10/032,700

Ref. No.: 659-911

Client Ref. No.: K-C 17154

11. (Currently Amended) The refastenable absorbent garment invention of claim 1 wherein said fastener member comprises a refastenable portion releasably engaging said body side of said second body panel.

12. (Currently Amended) The refastenable absorbent garment invention of claim 11 wherein said refastenable portion comprise an array of hook members.

13. (Currently Amended) The refastenable absorbent garment invention of claim 9 wherein said refastenable portion comprises an adhesive.

14. (Currently Amended) The refastenable absorbent garment invention of claim 1 wherein said first body panel is a rear body panel and wherein said second body panel is a front body panel.

15. (Currently Amended) The refastenable absorbent garment invention of claim 1 wherein said first and second body panels are integrally formed as portions of a one-piece body chassis.

16. (Original) A refastenable absorbent garment comprising:

a first body panel having a body side, a garment side and an outboard side edge;

a second body panel having a body side, a garment side and an outboard side edge; and

a fastener member comprising first and second portions each having an inboard and an outboard edge, wherein said first portion is attached to said body side of said first body panel and said second portion is releasably attached to said body side of said second body panel, and wherein said outboard edges of said first and second portions are hingedly connected.

S/N 10/032,700

Ref. No.: 659-911

Client Ref. No.: K-C 17154

17. (Currently Amended) The refastenable absorbent garment invention of claim 16 wherein said first portion of said fastener member is fixedly attached to said body side of said first body panel.

18. (Currently Amended) The refastenable absorbent garment invention of claim 17 wherein said first portion of said fastener member is bonded to said body side of said first body panel.

19. (Currently Amended) The refastenable absorbent garment invention of claim 16 wherein said first portion of said fastener member is releasably attached to said body side of said first body panel.

20. (Currently Amended) The refastenable absorbent garment invention of claim 16 wherein said first and second body panels are integrally formed as portions of a one-piece body chassis.

21. (Original) A method for assembling a refastenable absorbent garment comprising:

- providing a first body panel having a body side and a garment side;
- providing a second body panel having a body side and a garment side;
- providing a fastener member comprising a first and second portion each having a body side and a garment side, wherein said body side of said first portion faces said body side of said second portion and wherein said first and second portions are hingedly connected;

- applying said garment side of said first portion of said fastener member to said body side of said first body panel; and

- releasably applying said body side of said second body panel to said garment side of said second portion of said fastener member.

S/N 10/032,700
Ref. No.: 659-911
Client Ref. No.: K-C 17154

22. (Currently Amended) The method invention of claim 21 wherein applying said garment side of said first portion of said fastener member to said body side of said first body panel comprises fixedly securing said garment side of said first portion of said fastener member to said body side of said first body panel.

23. (Currently Amended) The method invention of claim ~~21~~ 22 wherein said fixedly securing said garment side of said first portion of said fastener member to said body side of said first body panel comprising bonding said garment side of said first portion of said fastener member to said body side of said first body panel.

24. (Currently Amended) The method invention of claim 21 wherein applying said garment side of said first portion of said fastener member to said body side of said first body panel comprises releasably securing said garment side of said first portion of said fastener member to said body side of said first body panel.

25. (Currently Amended) The method invention of claim 21 wherein each of said first and second body panels comprise an outboard side edge and wherein each of said first and second portions comprise an inboard and an outboard edge, wherein said outboard edges of said first and second portions are positioned closer to said outboard side edges of said first and second body panels, respectively, than are said inboard edges of said first and second portions, and wherein said outboard edges of said first and second portions are hingedly connected.

26. (Currently Amended) The method invention of claim 21 wherein said first and second portions comprise first and second folds hingedly connected along a folded edge.

S/N 10/032,700

Ref. No.: 659-911

Client Ref. No.: K-C 17154

27. (Currently Amended) The method invention of claim 21 wherein said first portion is bonded to said second portion.

28. (Currently Amended) The method invention of claim 21 wherein said first and second body panels are integrally formed as portions of a one-piece body chassis.

29. (Original) A method for manufacturing a refastenable absorbent garment comprising:

moving a first body panel web having a body side and a garment side in a machine direction;

moving a second body panel web having a body side and a garment side in a machine direction;

providing a plurality of fastener members each comprising a first and second portion, wherein said first and second portions each have a body side and a garment side;

successively applying said garment side of said first portions of said fastener members to said body side of said first body panel web; and

successively, releasably applying said body side of said second body panel web to said garment side of said second portions of said fastener members.

30. (Currently Amended) The method invention of claim 29 wherein each of said plurality of said first and second fastener members comprises a center region, and further comprising successively securing said center region of said first portions of said fastener members to said center region of said second portions of said fastener members, and successively cutting said first and second body panel webs and said first and second portions along said center regions of said first and second fastener members to form a plurality of discrete absorbent garments.

S/N 10/032,700
Ref. No.: 659-911
Client Ref. No.: K-C 17154

31. (Currently Amended) The method invention of claim 30 wherein said successively securing said center region of said first portions of said fastener members to said center region of said second portions of said fastener members comprises successively bonding said center region of said first portions of said fastener members to said center region of said second portions of said fastener members.

32. (Currently Amended) The method invention of claim 29 wherein said successively applying said garment side of said first portions of said fastener members to said body side of said first body panel web comprises successively bonding said garment side of said first portions of said fastener members to said body side of said first body panel web.

33. (Currently Amended) The method invention of claim 29 wherein said successively applying said garment side of said first portions of said fastener members to said body side of said first body panel web comprises successively releasably securing said garment side of said first portions of said fastener members to said body side of said first body panel web.

34. (Currently Amended) The method invention of claim 29 wherein said second portions of said fastener members each comprise an array of hooks, and wherein successively, releasably applying said body side of said second body panel web to said garment side of said second portions of said fastener members comprises successively, releasably engaging said body side of said second body panel web with said array of hooks.

35. (Currently Amended) The method invention of claim 34 wherein said second body panel comprises a landing material defining at least in part said body side thereof.

S/N 10/032,700
Ref. No.: 659-911
Client Ref. No.: K-C 17154

36. (Currently Amended) The method invention of claim 29 wherein said second portions of said fastener members each comprise an adhesive patch, and wherein successively, releasably applying said body side of said second body panel web to said garment side of said second portions of said fastener members comprises successively, releasably engaging said body side of said second body panel web with said adhesive patch.

37. (Currently Amended) The method invention of claim 29 wherein said first and second body panels are integrally formed as portions of a one-piece body chassis.

38. (Withdrawn) A method of using an absorbent garment comprising:
providing said absorbent garment comprising a first body panel having a body side and a garment side, a second body panel having a body side and a garment side, and a fastener member attached to said body side of said first body panel and releasably attached to said body side of said second body panel;
applying said garment to a user; and
disengaging said fastener member from said body side of said second body panel.

39. (Withdrawn) The invention of claim 38 further comprising releasably reengaging said fastener member with said body side of said second body panel.

40. (Withdrawn) The invention of claim 38 wherein said fastener member comprises a first portion attached to said body side of said first body panel and a second portion releasably attached to said body side of said second body panel, wherein said first and second portions are hingedly connected.